

A CTMC-Based Approach for UAV Maintenance Optimization: Balancing Cost and Availability

Dharmaraja Selvamuthu

Department of Mathematics
Indian Institute of Technology Delhi
New Delhi, India
dharmar@maths.iitd.ac.in

Sanya Sachan

Department of Mathematics
Indian Institute of Technology Delhi
New Delhi, India
mt1221286@maths.iitd.ac.in

Raina Raj

Bharti School of Telecommunication
Technology & Management, Indian Institute
of Technology Delhi, New Delhi, India
rainaraj.curaj@gmail.com

Abstract—This paper presents a Continuous-Time Markov Chain (CTMC) model to optimize UAV preventive maintenance, balancing cost and availability. By systematically analyzing the impact of varying preventive maintenance rates, we identify an optimal rate that minimizes long-term costs while maintaining desired availability. Our results demonstrate that a well-calibrated preventive maintenance strategy is essential for efficient UAV fleet operations. This study provides a quantitative framework for operators to improve maintenance scheduling decisions, offering actionable insights for real-world applications.

Index Terms—CTMC, UAV Maintenance, Stochastic Optimization, Preventive Maintenance

I. INTRODUCTION

Unmanned Aerial Vehicles (UAVs) are essential in diverse applications, including defense, surveillance, logistics, and disaster response. Assessing maintainability and reliability metrics in UAV-based surveillance systems is crucial, as system failures can lead to severe security breaches and data loss, particularly in high-risk scenarios. To enhance the reliability and operational efficiency of UAVs across industries, researchers have extensively studied advanced maintenance strategies and failure mitigation techniques. Ensuring high operational availability while minimizing maintenance costs is essential for effective UAV fleet management. An inefficient maintenance policy can lead to excessive downtime, unexpected failures, and high corrective maintenance costs, impacting mission success and overall operational efficiency. The UAV shown in Fig. 1 is MQ-1 Predator, used here for illustrative purposes.

UAV maintenance strategies typically fall into two broad categories: *reactive maintenance*, where failures are repaired as they occur, and *scheduled preventive maintenance*, where servicing is performed at fixed intervals [1]. However, determining the right frequency for preventive maintenance remains a critical challenge—too frequent maintenance increases costs and downtime, while infrequent maintenance increases the risk of failures. This work focuses on systematically determining an optimal preventive maintenance rate to balance cost and availability.



Fig. 1. MQ-1 Predator — one of the earliest armed UAVs, deployed since the 1990s for reconnaissance and targeted strikes

II. RELATED WORK

UAV maintenance strategies have been widely studied in the context of operational efficiency and cost optimization. Traditional maintenance policies can be broadly classified into *reactive maintenance*, where repairs are performed only after failures occur, and *scheduled preventive maintenance*, where servicing is carried out at fixed intervals [2]. While reactive maintenance can lead to unexpected failures and high corrective costs, scheduled preventive maintenance requires careful tuning to avoid unnecessary interventions and excessive downtime [3].

Several studies have explored logistics-based approaches to UAV maintenance, focusing on reliability and maintenance assessment. Petritoli et al. [4] built on the introduced a novel framework to establish more efficient maintenance scheduling strategies. Some research has highlighted the impact of degradation variability among functionally exchangeable units on overall system performance. Chai et al. [5] quantified the benefits of integrating reallocation into a condition-based maintenance framework, particularly for a 1-out-of-2 pairs balanced system—a configuration where the system remains operational as long as at least one pair of units is functional. This approach offers valuable insights into optimizing maintenance strategies for systems with interchangeable components.

To address the challenge of determining optimal maintenance intervals, researchers have explored probabilistic and stochastic modeling approaches. Markov-based mod-

els, including *Discrete-Time Markov Chains (DTMCs)* and *Continuous-Time Markov Chains (CTMCs)* [6], have been applied to reliability analysis and maintenance decision-making. These models provide a structured way to analyze system transitions between operational and maintenance states, enabling the evaluation of system performance under different maintenance policies. Lins et al. [7] employed stochastic modeling with Petri Nets to analyze the impact of integrating redundant components on UAV system availability.

Several studies have leveraged *Markov Decision Processes (MDPs)* and *Hidden Markov Models (HMMs)* to optimize maintenance scheduling, particularly in predictive maintenance frameworks where real-time sensor data is used to estimate system degradation. While data-driven methods such as machine learning have gained popularity, they often require extensive historical failure data and computationally expensive models. In contrast, a CTMC model provides a mathematically tractable approach to capturing system behavior and evaluating different maintenance policies without relying on large datasets.

In this work, we employ a *CTMC-based framework to analyze UAV maintenance policies*, focusing on the dependency between preventive maintenance frequency, system availability, and maintenance costs. Unlike predictive maintenance approaches, our method does not rely on real-time sensor data but instead provides a structured methodology for maintenance decision-making using transition rate analysis and optimization techniques.

To achieve this, we model the UAV's operational and maintenance transitions using a *Continuous-Time Markov Chain (CTMC)*. The CTMC framework allows us to analyze the UAV's movement between *Working (W)*, *Preventive Maintenance (PM)*, and *Corrective Maintenance (CM)* states, governed by transition rates. We perform *sensitivity analysis* to examine how different preventive maintenance rates ($q_{W,PM}$) affect system availability and cost. Using this analysis, we determine an *optimal* $q_{W,PM}$ that ensures UAV availability remains above a minimum threshold while minimizing overall maintenance costs.




Fig. 2. State-transition diagram for UAV maintenance

The key objectives of this work are as follows:

- Develop a CTMC model to represent UAV operational and maintenance states.
- Analyze the impact of varying preventive maintenance rates on UAV availability and total maintenance cost.
- Determine an optimal preventive maintenance rate $q_{W,PM}$ that minimizes cost while maintaining a required level of availability.

This paper is structured as follows: *Section III* details the CTMC model and simulation methodology. *Section IV* presents sensitivity analysis and optimization results. *Section V* discusses key findings and implications. Finally, *Section VI* concludes the paper and suggests future research directions.

III. METHODOLOGY

A. Continuous-Time Markov Chain Model

To model UAV maintenance and operational transitions, we use a *Continuous-Time Markov Chain (CTMC)*, where the system can be in one of three states:

- **Working (W):** The UAV is fully operational.
- **Preventive Maintenance (PM):** Scheduled maintenance is performed to reduce failure risks.
- **Corrective Maintenance (CM):** The UAV has failed and requires repairs before returning to operation.

The state transitions are governed by transition rates, represented in the transition rate matrix Q :

$$Q = \begin{bmatrix} -(q_{W,PM} + q_{W,CM}) & q_{W,PM} & q_{W,CM} \\ q_{PM,W} & -q_{PM,W} & 0 \\ q_{CM,W} & 0 & -q_{CM,W} \end{bmatrix} \quad (1)$$

where:

- $q_{W,PM}$: Transition rate from Working to Preventive Maintenance.
- $q_{W,CM}$: Transition rate from Working to Corrective Maintenance (failure rate).
- $q_{PM,W}$: Transition rate from Preventive Maintenance back to Working.
- $q_{CM,W}$: Transition rate from Corrective Maintenance back to Working.

B. Parameter Selection and Justification

The following parameters have been taken fixed based on literature and industry standards but they can be changed as per convenience :

- **Failure Rate** ($q_{W,CM} = 0.0005/\text{hour}$): This reflects the reliability of UAVs in high-risk operational scenarios, such as prolonged surveillance. This value aligns with observed failure data for small UAVs where subsystem failure rates vary widely depending on design and use case [8].
- **CM Repair Rate** ($q_{CM,W} = 0.05/\text{hour}$): This implies an average repair time of 20 hours, consistent with standard turnaround times reported in UAV maintenance operations, particularly those conducted at centralized repair facilities [9].

- **PM Repair Rate** ($q_{PM,W} = 0.1/\text{hour}$): Preventive maintenance tasks are typically less time-consuming, averaging around 10 hours. This is in line with field practices where minor servicing is performed on-site by operational personnel [9].
- **PM Cost** ($\text{cost}_{PM} = \$500$): This cost includes labor and consumables required for routine servicing. It falls within the typical range found in UAV logistics cost reports, which estimate preventive interventions to be relatively inexpensive [10].
- **CM Cost** ($\text{cost}_{CM} = \$10,000$): Corrective maintenance incurs significant costs due to the need for skilled labor, part replacements, and testing. Costs of this magnitude are common in post-failure recovery of UAV systems [9].

By fixing these values, the optimization focuses solely on determining the best preventive maintenance rate ($q_{W,PM}$) to minimize costs while maintaining an acceptable availability level.

C. Simulation Process

To analyze system performance, we simulate UAV operation over a fixed time horizon. Transitions between states are determined using an exponential distribution:

$$T = \frac{-\ln(U)}{\lambda} \quad (2)$$

where T is the time spent in a state, λ is the exit rate from the current state, and U is a uniform random variable in $(0,1)$.

At each step, we:

- 1) Determine the exit rate λ from the current state.
- 2) Sample a transition time from an exponential distribution.
- 3) Move to the next state based on transition probabilities.
- 4) Track system availability and maintenance costs over time.

D. Sensitivity Analysis and Optimization

To determine the optimal preventive maintenance rate $q_{W,PM}$, we perform a sensitivity analysis by varying its value over a range while keeping $q_{W,CM}$ fixed. The key performance metrics analyzed are:

- **Availability (%)** - Percentage of time the UAV remains in the Working state.
- **Total Maintenance Cost** - Sum of costs incurred due to both preventive and corrective maintenance events.

To select the optimal $q_{W,PM}$, we use a penalty-based objective function that ensures the penalty factor α effectively discourages solutions where availability falls below the required threshold:

$$J(q_{W,PM}) = C_{\text{total}} + \alpha \cdot \max(0, A_{\min} - A) \quad (3)$$

where:

- C_{total} is the total maintenance cost.
- $A_{\min}$ is the minimum required availability threshold.
- A is the observed availability from the simulation.

- α is a sufficiently large penalty factor to strongly discourage solutions where $A < A_{\min}$.

To ensure the effectiveness of α , we calibrate it based on the relative cost impact of reduced availability, ensuring that any violation of the availability threshold is significantly penalized. By systematically evaluating different values of $q_{W,PM}$, we determine the optimal rate that minimizes $J(q_{W,PM})$ while maintaining availability above the required threshold.

IV. RESULTS AND ANALYSIS

A. Sensitivity Analysis of Preventive Maintenance Rate

To evaluate the impact of preventive maintenance rate ($q_{W,PM}$) on UAV availability and maintenance cost, we conducted a sensitivity analysis by varying $q_{W,PM}$ over a range while keeping $q_{W,CM}$ fixed. The results are shown in Fig. 3.




Fig. 3. Effect of $q_{W,PM}$ on UAV availability and maintenance cost.

From the results, we observe the following trends:

- **Availability decreases** as $q_{W,PM}$ increases, since more frequent preventive maintenance causes additional down-time.
- **Maintenance cost initially decreases shortly then increases**, as preventive maintenance reduces costly failures. However, beyond a certain point, costs begin to rise due to excessive maintenance interventions.

B. Optimization Results

The optimization process determined the optimal preventive maintenance factor $q_{W,PM}$ to be ****0.0009****. This results in an ****availability of 98.19%**** while minimizing the total maintenance cost to ****\$10,995.00****. The objective function value is ****11,964.00****, suggesting that the cost is the dominant term in optimization.

Table I summarizes these findings.

TABLE I
OPTIMIZATION RESULTS

Parameter	Optimal Value
$q_{W,PM}$	0.0009
Availability (%)	98.19
Total Maintenance Cost (\$)	10,995.00




Fig. 4. Objective (Cost + Penalty) vs. $q_{W,PM}$

C. Discussion of Findings

Based on the analysis, the following key insights can be drawn:

- **Excessive preventive maintenance** ($q_{W,PM} > 0.002$) leads to diminished availability without significant cost savings. This highlights the importance of avoiding over-maintenance, which can strain resources without commensurate benefits.
- **Insufficient preventive maintenance** ($q_{W,PM} < 0.0008$) results in increased corrective maintenance costs, outweighing the savings from reduced preventive interventions. This underscores the need for a balanced approach to maintenance scheduling.
- **Optimal $q_{W,PM}$ ensures availability remains above 95%** while keeping total costs manageable. The selected rate of $q_{W,PM} = 0.0009$ strikes this balance, demonstrating the effectiveness of the CTMC framework in identifying cost-optimal policies.

These findings demonstrate that a well-calibrated preventive maintenance strategy is essential for optimizing UAV fleet operations. The results also highlight the critical role of parameter selection in achieving desired outcomes. For instance, the high corrective maintenance cost ($\text{cost}_{CM} = \$10,000$) and relatively low failure rate ($q_{W,CM} = 0.0005$) create a scenario where infrequent PM is cost-effective. However, in systems with higher failure rates or lower CM costs, the optimal $q_{W,PM}$ may shift significantly.

1) *Implications for UAV Operators:* The results provide actionable insights for UAV fleet operators:

- **Reliability Improvements:** Reducing the failure rate ($q_{W,CM}$) through better component design or operational practices can further enhance availability without increasing maintenance costs.
- **Cost Management:** Operators must carefully weigh the costs of preventive and corrective maintenance, as excessive PM can lead to unnecessary expenditures.

- **Adaptive Policies:** Integrating real-time health monitoring can enable dynamic adjustment of $q_{W,PM}$ based on system conditions, improving both cost efficiency and availability.

D. Additional analysis : Error rate and system stability

To validate the robustness of the proposed CTMC simulation, we analyzed the throughput of maintenance events and error rate (variance) in availability.

Over a 10,000-hour simulation horizon, the average number of corrective maintenance events dropped from 35 to 11 as $q_{W,PM}$ increased from 0.0005 to 0.0015. This indicates that preventive interventions significantly reduce failure occurrences.

Furthermore, the standard deviation in availability across 20 simulation runs remained under 0.3% for the optimal $q_{W,PM} = 0.0009$, suggesting that the system's performance is stable and not sensitive to minor fluctuations in parameters.

E. Comparison with Related Work

Several studies have addressed UAV maintenance optimization using diverse approaches. Lee and Martinez [1] and Smith and Johnson [3] focus on predictive techniques driven by telemetry data, while Wilson et al. [2] and Brown [6] employ stochastic modeling frameworks, including Markov chains.

Petritoli et al. [4] and Chai et al. [5] emphasize degradation and redundancy in system design, often requiring high-resolution diagnostics. Lins et al. [7] apply stochastic Petri nets to assess drone reliability.

In contrast, our CTMC-based approach offers a lightweight, data-efficient alternative, enabling effective maintenance scheduling without reliance on real-time sensors.

V. CONCLUSION

In this paper, we developed a *Continuous-Time Markov Chain (CTMC)* model to optimize UAV maintenance strategies by analyzing the dependency between preventive maintenance frequency, system availability, and total maintenance cost. The CTMC framework provided a structured and mathematically tractable approach to evaluating maintenance policies, enabling us to identify an optimal preventive maintenance rate ($q_{W,PM}$) that balances cost and availability.

Our sensitivity analysis demonstrated that increasing preventive maintenance frequency ($q_{W,PM}$) initially reduces total maintenance costs by preventing failures. However, beyond a certain threshold, excessive preventive maintenance leads to increased costs and reduced availability. By applying a penalty-based objective function, we identified an optimal preventive maintenance rate of $q_{W,PM} = 0.0009$, which ensures an availability of 98.19% while minimizing total maintenance expenditures to \$10,995.00.

Key findings of this study include:

- A well-calibrated preventive maintenance rate is essential for balancing availability and cost.
- Excessive preventive maintenance ($q_{W,PM} > 0.002$) leads to unnecessary downtime and higher costs, while

insufficient preventive maintenance ($q_{W,PM} < 0.0008$) results in increased corrective maintenance costs. This highlights the importance of a balanced approach to maintenance scheduling.

- The CTMC-based approach provides a structured method for optimizing UAV maintenance policies without requiring large-scale failure data. By leveraging transition rate analysis and sensitivity analysis, the model offers a flexible framework adaptable to various operational scenarios.

Implications for UAV Operators: The results of this study provide actionable insights for UAV fleet operators:

- **Reliability Improvements:** Reducing the failure rate ($q_{W,CM}$) through better component design or operational practices can further enhance availability without increasing maintenance costs.
- **Cost Management:** Operators must carefully weigh the costs of preventive and corrective maintenance, as excessive PM can lead to unnecessary expenditures.
- **Adaptive Policies:** Integrating real-time health monitoring can enable dynamic adjustment of $q_{W,PM}$ based on system conditions, improving both cost efficiency and availability.

Future Work: This study lays the foundation for several extensions:

- **Real-World Data Integration:** Incorporating field data to refine transition rates and cost structures, ensuring the model reflects actual operational conditions.
- **Machine Learning Techniques:** Leveraging predictive maintenance frameworks to dynamically adjust $q_{W,PM}$ based on real-time system health data.
- **Mission-Critical Constraints:** Exploring scenarios where availability requirements are stricter (e.g., 99%) and evaluating the impact on maintenance costs and policies.

This research provides a quantitative framework for UAV fleet operators to improve maintenance planning and decision-making, contributing to more efficient and cost-effective UAV operations.

REFERENCES

- [1] E. Lee and F. Martinez, "Optimization techniques for uav maintenance policies," in *Proceedings of the IEEE Aerospace Conference*, 2020, pp. 345–356.
- [2] D. Wilson, M. Green, and R. Patel, "Balancing cost and availability in maintenance systems," in *Proceedings of the International Conference on Operations Research*, 2021, pp. 101–110.
- [3] A. Smith and B. Johnson, "Optimizing uav maintenance strategies," *IEEE Transactions on Aerospace and Electronic Systems*, vol. 45, no. 2, pp. 123–135, 2023.
- [4] E. Petritoli, F. Leccese, and L. Ciani, "Reliability and maintenance analysis of unmanned aerial vehicles," *Sensors*, vol. 18, no. 9, p. 3171, 2018.
- [5] X. Chai, O. A. Kilic, J. Veldman, R. H. Teunter, and X. Zhao, "Condition-based reallocation and maintenance for a 1-out-of-2 pairs balanced system," *European Journal of Operational Research*, vol. 318, no. 2, pp. 618–628, 2024.
- [6] C. Brown, "Markov chain models for reliability analysis," *Journal of Stochastic Systems*, vol. 12, no. 4, pp. 220–235, 2022.
- [7] L. Lins, E. Nascimento, J. Dantas, J. Araujo, and P. Maciel, "Stochastic modeling for assessing the reliability and availability of drone-based surveillance systems," in *2024 IEEE International Systems Conference (SysCon)*. IEEE, 2024, pp. 1–8.
- [8] F. J. Garcia, "Reliability analysis of uav components based on field data," *Journal of Aerospace Systems*, vol. 15, no. 3, pp. 245–258, 2018.
- [9] B. Hobbs and D. Herwitz, "Preliminary human factors evaluation of small unmanned aerial vehicles," NASA Ames Research Center, Tech. Rep., 2003. [Online]. Available: https://human-factors.arc.nasa.gov/publications/UAV_interimreport_Hobbs_Herwitz.pdf
- [10] VillageReach, "Malawi uas project: Final report for ministry of health," Tech. Rep., 2016. [Online]. Available: https://www.villagereach.org/wp-content/uploads/2017/06/Malawi-UAS-Report_MOH-Draft_FINAL_14_07_16.pdf